




BLU 80 mm

DESCRIPTION: Paver **TEXTURE:** Smooth and HD² Smooth

PALLET OVERVIEW



NOTES

See page 54 to 56 for more technical information. When used in a permeable pavement application, see page 93 to 97 for more technical information.

See page 21 for more information about applications.

JOINT WIDTH: 9/32" (7 mm)
% OF SURFACE OPENING: 4.5%**
INFILTRATION RATE: 570 in./hr
 (14 475 mm/hr)

**For permeable application, the installation should be combined with Blu 6x13 in a modular pattern. A min. of 4.5% opening surface requires 75% of Blu 6x13 and 25% of Blu.


Specifications per pallet	Imperial	Metric
Cubing	84.96 ft²	7.90 m ²
Approx. Weight Smooth	3 095 lbs	1 404 kg
Approx. Weight Smooth HD ²	3 280 lbs	1 488 kg
Number of rows	8	
Coverage per row	10.62 ft ²	0.99 m ²
Linear coverage per row	9.75 lin. ft	2.97 lin. m

Unit dimensions	in	mm	Units/pallet
Height	3 1/8	80	32 units
Width	13	330	
Length	6 1/2	165	


Height	3 1/8	80	32 units
Width	13	330	
Length	13	330	

Height	3 1/8	80	16 units
Width	13	330	
Length	19 1/2	495	


01 | Modular pattern



02 | Modular pattern



03 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chestnut Brown

HD² Smooth
Smooth



Champlain Grey

HD² Smooth
Smooth



Caffè Crema

HD² Smooth




Beige Cream

Smooth



Greyed Nickel

HD² Smooth
Smooth



Shale Grey

HD² Smooth
Smooth



Onyx Black

HD² Smooth
Smooth

