














# **PARA** 500 × 250 & 500 × 500

**DESCRIPTION:** Slab **TEXTURE:** HD<sup>2</sup> Smooth

# Pallet Overview - 500 × 250

A	

### Pallet Overview - 500 × 500







Specifications per pallet		Imperial	Metric	
	Product dimension (L×w×H)		$9^{13}\%6 \times 19^{11}\%6 \times 2^{3}\%$	250 × 500 × 60
88 units / pallet	Cubing		118.40 ft²	11 m²
	Approx. Weight		3 422 lbs	1 552 kg
	Number of rows		11	
	Coverage per row		10.76 ft <sup>2</sup>	1 m <sup>2</sup>
	Lin. coverage		6.56 lin. ft	2 lin. m
per row	per row	Length	13.12 lin. ft	4 lin. m
Specifications per pallet		Imperial	Metric	
	Product dimension (L×W×H)		19 ½6 × 19 ½6 × 2 %	500 × 500 × 60
The second second	Cubing		118.40 ft <sup>2</sup>	11 m <sup>2</sup>


	Product dimension $(L \times W \times H)$	$19{}^{1}\!\!/_{6}\!\times 19{}^{1}\!\!/_{6}\!\times 2{}^{3}\!\!/_{8}$	$500\times500\times60$
	Cubing	118.40 ft <sup>2</sup>	11 m²
44 units / pallet	Approx. Weight	3 403 lb	1 544 kg
	Number of rows	11	
	Coverage per row	10.76 ft <sup>2</sup>	1 m <sup>2</sup>
	Linear coverage per row	6.56 lin. ft	2 lin. m

# Laying Patterns Options


01 | Linear 02 | Linear







13 | Modular



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

### **NOTES**

### **Pedestal Set Application:**

Para 500x500 can be used with pedestals at each corner (pedestrian use only). Allowable load Capacity of slab on pedestal set (including a safety factor of 2): 1 300 lb (590 kg)

See page 6 for icons description.

See page 16 for more information about

See page 26 to 28 for more technical information.

\*For this application, it is recommended that this product be installed on a concrete base as designed by a local Engineer.



# **PARA** 500 × 750

**DESCRIPTION:** Slab **TEXTURE:** HD<sup>2</sup> Smooth











Specifications pe	r pallet
	Produc
	Cubin
22 units / pallet	Approx

Product dimension (I	$\bot \times W \times H$ )	29 ½ × 19 ½ <sub>6</sub> × 2 ¾	750 × 500 × 60
Cubing		88.80 ft <sup>2</sup>	8.25 m <sup>2</sup>
Approx. Weight		2 537 lbs	1 151 kg
Number of rows		11	
Coverage per row		8.07 ft <sup>2</sup>	0.75 m <sup>2</sup>
Lin. coverage per row	Depth	3.28 lin. ft	1 lin. m
	Length	4.92 lin. ft	1.50 lin. m

Imperial

Metric


# Pallet Overview

# Silver Granite Onyx Black Greyed Nickel Caffè Crema Beige Cream HD² Smooth HD² Smooth HD² Smooth HD² Smooth

# **Laying Patterns Options**

06   Linear	07   Linear	08   Linear	09   Herringbone

10 | Linear



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

# **NOTES**

See page 6 for icons description.
See page 16 for more information about applications.

See page 26 to 28 for more technical information.

Allowable load Capacity of slab on pedestal set (including a safety factor of 2): 1135 lb (514 kg)